# SCHMERSAL Tech Briefs: **One Giant Leap for Safety: AZM400**



CE

։(Ա)ս։

# Features



Motor driven locking bolt extends and retracts in switch



Actuator alignment tolerances: Hole dia. is 8 mm wider than bolt 1 mm - 7 mm offset from switch



Emergency Exit knob (T) manually retracts bolt



3 Color LED Display Green: Power, not actuated Yellow: Actuation Red: (Flashing) Diagnostic error

### **Overview**

The AZM400 is a safety rated motorized bolt lock with an integrated radio frequency identification (RFID) based electronic safety sensor.

### **Operating Principle**

The Aluminum die-cast body contains the RFID sensor and a motor-driven locking bolt, which fits into the hole of the actuator block with the matching RFID target. Once locked, the solenoid bolt provides a locking force of 10,000 N. The motorized AZM400 is a bi-stable system, thus in the event of a power failure the switch maintains the last locked status of the interlock.

In addition, the AZM400 uses RFID to detect the actuator and indicate a closed guard. This non-contact operating principle limits wear on components, tolerates misalignment, and offers the option of individual coding.

### Intelligent locking

The AZM400 can detect if the locking bolt has been blocked from reaching a "locked" state. Before reporting a fault the switch will make a second autonomous attempt at locking, therefore reducing the number of error messages and protecting the device and machine against damage.

### Safety Classification

The AZM400 series is compliant with North American and International standards such as cULus and CE. It's two-channel input signal meets PLe/ Category4 (ISO 13849) or SIL3 (IEC 61508) for both its interlock and guard locking function. It is a Type 4 interlock per ISO 14119, with a high coding level with the individual coding option (I1 or I2).

### Available Features and Options

- Visual diagnostics via 3 LEDs
- 1 or 2 auxiliary outputs for enhanced diagnostics
- M12 connector
- Manual override or emergency exit knob for bolt retraction
- Electronic release via auxiliary power supply Individual coding options I1: one time teaching process
  - 12: Re-teaching possible, 10 minute delay

### Electric Manual Release (ST2...E)

The AZM400 is power-to-lock and power-to-unlock. It is available with an optional electric manual release making it possible to release the device

in the event of a power failure or if the main supply is switched off. This version has an additional diagnostic output and is fitted with an additional 5-pole M12 connector to allow for connection to an auxiliary voltage supply.

# **Applications**

- Machine Tools
- Packaging machinery
- Robot cells
- Printing machines
- Injection molding
- CNC Machines
- Assembly Equipment





AZM400 Brochure, 10 pages

# **Ordering Details**

### AZM400Z-ST-0-1P2P-@ AZM400Z-ST2-0-2P2P-@-E

### ① Actuator Coding

- blank Standard version (no coding)
- Individual coding (single) 11
- Individual coding (repeatable) 12

#### ② Manual release blank Manual release Т

Emergency Exit knob

Regularly stocked models: AZM400Z-ST-1P2P AZM400Z-ST-1P2P-T

AZM400Z-ST2-2P2P-E AZM400Z-ST2-2P2P-T-E

AZM400Z-ST-I2-1P2P AZM400Z-ST-I2-1P2P-T

AZM400Z-ST2-I2-2P2P-E

## Accessories

Actuators AZM400-B1 Standard Actuator

**Mounting bracket** MS-AZM400 Metal spacers

Manual override key AZM KEY Triangle key (M5)

### **Connector cables**

Main cable (M12, 8 pole) A-K8P-M12-S-G-5M-BK-2-X-A-4 A-K8P-M12-S-G-10M-BK-2-X-A-4

Second cable for ST2 (M12, 5 pole) A-K5P-M12-S-G-5M-BK-2-X-A-4 A-K5P-M12-S-G-10M-BK-2-X-A-4

#### **Compatible Safety Controllers**

SRB-301MA	SRB-301MC
SRB-301ST-24	SRB-301LCB
SRB-504ST	SRB-211ST
SRB-324ST	SRB-031MC

Bold part numbers are regularly stocked

# Contact

Switches Unlimited sales@switchesunlimited.com Phone: 800-221-0487 Fax:718-672-6370 www.switchesunlimited.com