



P-Nut ® Push-in Wire Connectors



Housing Material: Durable, flame resistant Polyamide 6.6, V2 rated.

Temp Range: -40° C to 105° C
UL approved up to 150° C.

Clamping Spring: Constructed of high tensile stainless steel. Provides constant pressure, even under high heat and/or chemical exposure.

Rated Voltage: UL Listed for 600 V max. for building wire. 1000 V max. for signs and fixtures. Current rated to largest conductor used.



P-NUTS ® are simple, safe and easy to use and test!

| Part # | Ports | Wire Range | Wire Strip Length |
|------------------------|-------|--|-------------------|
| 2003/1.5/3 Grey | 3 | 20-16 AWG Solid CU 20-16 AWG Tinned-Stranded CU | 10 mm |
| 2003/2.5/3 Orange | 3 | 20-12 AWG Solid CU 20-16 AWG Tinned-Stranded CU | 10 mm |
| 2003/2.5/3.00 Black | 3 | 20-12 AWG Solid CU 20-16 AWG Tinned-Stranded CU | 10 mm |
| 2003/2.5/3.15 Red | 3 | 20-12 AWG Solid CU 20-16 AWG Tinned-Stranded CU | 10 mm |
| 2003/2.5/3.03 White | 3 | 20-12 AWG Solid CU 20-16 AWG Tinned-Stranded CU | 10 mm |
| 2002/2.5/4 Blue | 4 | 18-12 AWG Solid CU 18-16 AWG Tinned-Stranded CU | 9 mm |
| 2001/2.5/5 Orange | 5 | 18-12 AWG Solid CU 18-16 AWG Tinned-Stranded CU | 11 mm |
| 2001/1.5/6 Grey | 6 | 22-16 AWG Solid CU 22-16 AWG Tinned-Stranded CU | 10 mm |



Strip it



Push it



Test it